



SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE, 8" (20.3cm) DIAMETER**
 Part Number: **9500-15EX, 9500-25EX**
 Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- -65°F to 250°F (-53°C to 121°C) temperature range
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs
- Meets requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

Part No.	Diameter	Length	End-Straps
9500-15EX	8" (20.3cm)	15' (4.57m)	Dual
9500-25EX	8" (20.3cm)	25' (7.62m)	Dual

ACCESSORIES:

Part No.	Ducting Size	Description
9500-01	8" (20.3cm)	Duct to Duct Connector, with raised lip
9500-35	8" (20.3cm)	Storage Rack for 8" (20.3cm) Ducting, up to 25' (7.62m) Ducting
9500-45	8" (20.3cm)	Storage Bag
9600-50EX	8" (20.3cm)	Reducer, Statically conductive for 16" (40.6cm) blower



SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE**
 Part Number: **9550-15EX, 9550-25EX**
 Style: **12" (30.4cm) RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- Temperature resistant up to 250°F (121°C)
- Retractable, non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs
- Meet requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end

AVAILABLE:

Part No	Diameter In (cm)	Length Ft (m)	End-Straps
9550-15EX	12" (30.4)	15' (4.57)	Dual
9550-25EX	12" (30.4)	25' (7.62)	Dual



ACCESSORIES:

Part No.	Ducting Size	Description
9550-01	12" (30.4)	Duct to duct connector with raised lip
9600-36	12" (30.4)	Storage rack for 12" (30.4) ducting up to 25' (7.62m) ducting
9600-45	12" (30.4)	Duct storage bag



SPECIFICATIONS

Product Description: **DUCTING, STATICALLY CONDUCTIVE, 16”(40.6cm) DIAMETER**
Part Number: **9600-15EX, 9600-25EX**
Style: **RETRACTABLE**

GENERAL DESCRIPTION:

This product is lightweight, retractable and designed for maximum air handling capabilities. Dual direction flow with low friction loss while providing a safe positive means of discharging static build-up.

CONSTRUCTION:

- Vinyl and polyester materials
- Single-Ply
- Neoprene coated
- Temp resistant up to -65°F to 250°F (-53°C to 121°C)
- Retractable, Non-collapsible design.
- Class 1 hard drawn spring steel wire helix
- Meets ASTM 227 Specs.
- Meet requirements of UL-94-VO
- Rated to 100,000 OHMS or less per square inch
- Integrated with extended solid grounding wire at each end



AVAILABLE:

Part No.	Diameter In (cm)	Length Ft (m)	End-Straps
9600-15EX	16” (40.6)	15’ (4.57)	Dual
9600-25EX	16” (40.6)	25’ (7.62)	Dual

ACCESSORIES:

Part No.	Ducting Size In (cm)	Description
9600-01	16” (40.6)	Duct to duct connector, with raised lip
9600-36	16” (40.6)	Storage rack for 16” ducting, up to 25’ (7.62m) ducting
9600-45	16” (40.6)	Duct storage bag
9600-50EX	8” (20.3)	Reducer, statically conductive for 16” (40.6m) blower to 8” (20.3m) ducting